

DRENEC SMOCK GLENTEX

Technical data

Surrounding hood with

integrated visor and

PROTECTION FRAMEWORK / EN 343: 2003 + A1: 2007

This garment is designed to protect from bad weather, precipitations in the form of rain or snow, fog, spray and moisture on the ground.

For professional use: Fishing - agriculture - industry - cleaning or other activities requiring this kind of protection.

THIS ARTICLE IS A

CATEGORY 1 PPF

And complies with EU regulation 2016/425

PPE = Personal Protective Equipment

PERFORMANCE



The assembled parts are High Frequency welded, guaranteeing a waterproof garment.

- Water penetration resistance ≥ 13,000 Pa = Class 3
- Evaporative resistance = n/a Ret > 40 m^2 .Pa/W= Class 1

RESTRICTIONS ON USE

(specified in the EN 343: 2007 standard)

"A maximum continuous wear time is recommended for 1 full suit (jacket + trousers) without a thermal lining"

Ambient work	Time
temperature in °C	in minutes
25	60
20	75
15	100
10	240
5	Unlimited

ILLUSTRATION AND INSTRUCTIONS Gusset with self-grip adjustment tab



Chest pocket with double self-grip flap.



PRINCIPAL MATERIALS

Glentex fabric - 320 g/m² Composition: 80 % PVC - 20 % Polyester Coated on one side

Features:

- COMFORTABLE
- LIGHT

- WATERPROOF

INSTRUCTIONS



- **STORAGE**
- Do not leave in package in damp surroundings.
- Store in dry surroundings at room temperature.
- Keep away from strong heat and flames.

For maximum protection, the DRENEC GLENTEX smock can be worn with PPE classed trousers or bib & braces.

SIZE TABLE

Drawstring at bottom

of garment

Size		e person's body in cm)	Guideline measurements of clothing (in cm)	
	Stature	Chest size	Chest size	
XS	150-165	78-86	120	
S	165-170	86-94	134	
M	170-180	94-102	144	Colour: dark yellow, green
L	175-185	102-110	160	
XL	180-190	110-124	168	<u>Sizes:</u> XS – S – M – L – XL – XXL
XXL	185+	124-134	182	

The lifespan of the garment is linked to conditions of use and the quality of its care.

Elasticated rib trim and gusset cuffs